

INDUSTRIAL COMPONENT DATA

T5B-1-SOND*/I4/SVB-SW 207512 Y7-207512 EATON ELECTRIC

Non-standard switch, T5B, 63 A, surface mounting, 1 co..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-1-SOND*/I4/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-1-SOND*/I4/SVB-SW
Catalog number	Y7-207512
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-7DF02E684A
Generated	2026-08-03

Product Overview

Non-standard switch, T5B, 63 A, surface mounting, 1 contact unit(s)

T5B-1-SOND*/I4/SVB-SW

Non-standard switch, T5B, 63 A, surface mounting, 1 contact unit(s), STOP function, With black rotary handle and locking ring

Non-standard switch, Product range: Non-standard switch, Part group reference: T5B, Stop Function: STOP function, With black rotary handle and locking ring, Notes: customized version according to form, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Non-standard switch, T5B, 63 A, surface mounting, 1 contact unit(s), STOP function, With black rotary handle and locking ringNon-standard switch, Product range: Non-standard switch, Part group reference: T5B, Stop Function: STOP function, With black rotary handle and locking ring, Notes: customized version according to form, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeNon-standard switchPart group referenceT5BStop FunctionSTOP functionWith black rotary handle and locking ringNotescustomized version according to formDegree of ProtectionIP65Designsurface mountingMotor rating

AC-23A, 50 - 60 Hz [P]400 V [P]30 kW Rated uninterrupted current [I_u]63 A Note on rated uninterrupted current I_u Rated uninterrupted current I_u is specified for max. cross-section. Number of contact units 1 contact unit(s) Technical data General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204 Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Enclosed -25 - +40 °C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [U_{imp}]6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [U_e]...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-1-SOND*/I4/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.