

INDUSTRIAL COMPONENT DATA

T5B-4-8213/X 092110 Y7-92110 EATON ELECTRIC Changeover switch, 4p, Ie 63A, 1-0-2, 45°, maintained, replacement switch

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-8213/X



Manufacturer	EATON - MOELLER
MPN / Reference	T5B-4-8213/X
Catalog number	Y7-92110
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-5F9F105C80
Generated	2026-08-02

Product Overview

Changeover switch, 4p, Ie=63A, 1-0-2, 45°, maintained, replacement switch

Switch 4-pole 63 A Indicator plate: 1-0-2 60°

Changeoverswitches, T5B, 63 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 60 °, design no. 8213

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Changeoverswitches, T5B, 63 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 60 °, design no.

8213Changeover switch, Product range: Control switches, Part group reference: T5B, Contacts: 8, Design: rear mounting, Basic switch, Switching angle: 60 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 30 kW, Rated uninterrupted current: Iu = 63 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3Delivery program

Product rangeControl switchesPart group referenceT5BBasic functionChangeoverswitchesContacts8Designrear mounting Basic switchContact sequenceSwitching angle60 °Design number8213Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]30 kWRated uninterrupted current [Iu]63 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units4 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40

°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock

resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V
ACElectrical characteristicsRated uninterrupted current [Iu]63 AElectrical characteristicsNo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-8213/X with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.