


INDUSTRIAL COMPONENT DATA

T8-3-8212/E/HI12 214782 Y7-214782 EATON ELECTRIC Changeoverswitches, Contacts: 9, 315 A, front plate: 1-0-2,..

Brand: EATON - MOELLER | Manufacturer Part Number: T8-3-8212/E/HI12



Manufacturer	EATON - MOELLER
MPN / Reference	T8-3-8212/E/HI12
Catalog number	Y7-214782
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-650479B29F
Generated	2026-08-04

Product Overview

Changeoverswitches, Contacts: 9, 315 A, front plate: 1-0-2, 60 °, maintained, flush mounting

T8-3-8212/E/HI12

Eaton Moeller® series T8 Changeoverswitches, T8, 315 A, flush mounting, 3 contact unit(s), Contacts: 9, 60 °, maintained, With 0 (Off) position, 1-0-2, Design number 8212

Changeover switch, Product range: Control switches, Part group reference: T8, with black thumb grip and front plate, Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 1-0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 132 kW, Rated uninterrupted current: Iu = 315 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T8 Changeover switch Catalog Number 214782 Model Code T8-3-8212/E/HI12 EAN 4015082147822 Product Length/Depth 130 mm Product Height 210 mm Product Width 130 mm Product Weight 3.02 kg

Certifications IEC/EN 60947

VDE 0660

IEC/EN 60204

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 214782 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

315 A

Rated operation current I_e at AC-3, 400 V (EF001392)

105 A

Rated operation power at AC-3, 400 V (EF001364)

55 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF001596)

Plastic

Type of control element (EF006976)

Short thumb-grip

Type of electrical connection of main circuit (EF006819)

Screw connection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T8-3-8212/E/HI12 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.