

INDUSTRIAL COMPONENT DATA

TM-2-8292/EZ 015096 Y7-15096 EATON ELECTRIC ON-OFF switches, Contacts: 3, 10 A, front plate: 0-1, 90 °, main..

Brand: EATON - MOELLER | Manufacturer Part Number: TM-2-8292/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	TM-2-8292/EZ
Catalog number	Y7-15096
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-9F97878639
Generated	2026-08-01

Product Overview

ON-OFF switches, Contacts: 3, 10 A, front plate: 0-1, 90 °, maintained, centre mounting

ON-OFF Disconnect Switch 3 Pole 10 A Faceplate 0-1 90°

Eaton Moeller® series TM ON-OFF switches, TM, 10 A, center mounting, 2 contact unit(s), Contacts: 3, 90 °, maintained, With 0 (Off) position, 0-1, Design number 8292

On-Off switch, Product range: Control switches, Part group reference: TM, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 3 kW, Rated uninterrupted current: I_u = 10 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, CSA, UL, Control switch as per IEC/EN 60947-5-1, Auxiliary switch as per IEC/EN 60947-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series TM On-off switch Catalog Number 015096 Model Code TM-2-8292/EZ EAN 4015080150961 Product Length/Depth 87 mm Product Height 30 mm Product Width 30 mm Product Weight 0.043 kg

Certifications Certified by UL for use in Canada

UL Category Control No.: NLRV

IEC/EN 60947-3

CSA-C22.2 No. 94

CSA
UL 508
CSA-C22.2 No. 14-05
IEC/EN 60947
CE
UL report applies to both US and Canada
IEC/EN 60947-5-1
VDE 0660
UL
UL File No.: E36332
ETIM for 015096 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
No
Version as maintenance-/service switch (EF006986)
No
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage Ue AC (EF007355)
500 V
Rated operating voltage (EF001435)
500 V
Rated permanent current Iu (EF001389)
10 A
Rated permanent current at AC-21, 400 V (EF009165)
0 A
Rated operation power at AC-3, 400 V (EF001364)
0 kW
Rated short-time withstand current Icw (EF007050)
0 kA
Rated operation power at AC-23, 400 V (EF007027)
3 kW
Switching power at 400 V (EF009166)
0 kW
Conditioned rated short-circuit current Iq (EF001444)
0 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF001377)
0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TM-2-8292/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.