

INDUSTRIAL COMPONENT DATA

T0-1-15111/E 067323 Y7-67323 EATON ELECTRIC Two-way switch, Contacts: 4, 20 A, front plate: 2-1-2-1, 90 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-15111/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-15111/E
Catalog number	Y7-67323
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-F0BBB84353
Generated	2026-08-01

Product Overview

Two-way switch, Contacts: 4, 20 A, front plate: 2-1-2-1, 90 °, maintained, flush mounting

Two-way switch 4-pole 20 A Indicator plate: 2-1-2-1 90

Eaton Moeller® series T0 Two-way switch, T0, 20 A, flush mounting, 1 contact unit(s), Contacts: 4, 90 °, maintained, Without 0 (Off) position, 2-1-2-1, Design number 15111

Two-way switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 2-1-2-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Two-way switch Catalog Number 067323 Model Code T0-1-15111/E EAN 4015080673231 Product Length/Depth 76 mm Product Height 48 mm Product Width 48 mm Product Weight 0.083 kg

Certifications CE

CSA Class No.: 3211-05

IEC/EN 60947

UL 60947-4-1

CSA

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332

IEC/EN 60947-3

UL

UL Category Control No.: NLRV

VDE 0660

CSA File No.: 012528

CSA-C22.2 No. 94

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 067323 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

On/Off switch

Number of poles (EF001391)

1

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-15111/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.