

INDUSTRIAL COMPONENT DATA

T0-1-15434/Z 072078 Y7-72078 EATON ELECTRIC

Changeoverswitches, Contacts: 2, With spring-return from HAND, 2..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-15434/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-15434/Z
Catalog number	Y7-72078
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-E06C252BD3
Generated	2026-08-03

Product Overview

Changeoverswitches, Contacts: 2, With spring-return from HAND, 20 A, front plate: HAND>0-AUTO, 45 °, momentary/maintained, rear mounting

2-Pole Switch Switch With Return From Hand 20 To Plate

Eaton Moeller® series T0 Changeover switches, T0, 20 A, rear mounting, 1 contact unit(s), Contacts: 2, With spring-return from HAND, 45°, momentary/maintained, With 0 (Off) position, With spring-return to 0, HAND>0-AUTO, Design no. 15434 Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Spring-return: With spring-return from HAND, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to 0, 1 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: HAND>0-AUTO

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 072078 Model Code T0-1-15434/Z EAN 4015080720782 Product Length/Depth 118 mm Product Height 48 mm Product Width 48 mm Product Weight 0.112 kg Certifications UL

UL 60947-4-1
CSA Class No.: 3211-05
CSA File No.: 012528
UL Category Control No.: NLRV
CSA
UL File No.: E36332
CE
VDE 0660
IEC/EN 60947-3
IEC/EN 60204
CSA-C22.2 No. 94
IEC/EN 60947
CSA-C22.2 No. 60947-4-1-14 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 072078 Low-voltage industrial controls and switchgear (EC002611)
Feature Name
Feature Value
Type of switch (EF003496)
Reverser
Number of poles (EF001391)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated permanent current Iu (EF001389)
20 A
Number of switch positions (EF000231)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
Yes
Device construction (EF008240)
Built-in device
Width in number of modular spacings (EF002950)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
Yes
Complete device in housing (EF007317)
No
Type of control element (EF006976)
Toggle
Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-15434/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.