

## INDUSTRIAL COMPONENT DATA

# T0-1-15441/E 009281 Y7-9281 EATON ELECTRIC

## Changeoverswitches, Contacts: 2, 20 A, front plate: 1-2, 90 °, ma..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-15441/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-1-15441/E    |
| Catalog number  | Y7-9281         |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-68589D15A6   |
| Generated       | 2026-08-01      |

### Product Overview

Changeoverswitches, Contacts: 2, 20 A, front plate: 1-2, 90 °, maintained, flush mounting

Switch Switch. 2 poles. 20 A. Indicator plate: 1-2. 90 °.

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, flush mounting, 1 contact unit(s), Contacts: 2, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 15441

Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, 1 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 1-2

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

### Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 009281 Model Code T0-1-15441/E EAN 4015080092810 Product Length/Depth 76 mm Product Height 48 mm Product Width 48 mm Product Weight 0.083 kg

Certifications CSA Class No.: 3211-05

CSA-C22.2 No. 94

UL

UL Category Control No.: NLRV

CE

CSA File No.: 012528

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

CSA

UL File No.: E36332

IEC/EN 60947-3

UL 60947-4-1

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second

ETIM for 009281 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

1

Max. rated operation voltage U<sub>e</sub> AC (EF007355)

690 V

Rated permanent current I<sub>u</sub> (EF001389)

20 A

Number of switch positions (EF000231)

2

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / T0-1-15441/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.