

INDUSTRIAL COMPONENT DATA

T0-10-8374/E 009922 Y7-9922 EATON ELECTRIC

Changeoverswitches, Contacts: 20, 20 A, front plate: 1-2, 90 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-10-8374/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-10-8374/E
Catalog number	Y7-9922
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-CC082914F3
Generated	2026-08-01

Product Overview

Changeoverswitches, Contacts: 20, 20 A, front plate: 1-2, 90 °, maintained, flush mounting

Switch Switch 20 poles 20 A Indicator plate: 1-2 90°

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, flush mounting, 10 contact unit(s), Contacts: 20, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 8374

Changeover switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 20, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, front plate: 1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 10 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 009922 Model Code T0-10-8374/E EAN 4015080099222 Product Length/Depth 162 mm Product Height 48 mm Product Width 48 mm Product Weight 0.274 kg

Certifications CSA

VDE 0660

UL File No.: E36332

CSA Class No.: 3211-05

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

UL 60947-4-1

UL

CE

IEC/EN 60947-3

CSA File No.: 012528

IEC/EN 60947

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 009922 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

10

With zero (off) position (EF001416)

false

With retraction in 0-position (EF002428)

false

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

false

Suitable for front mounting (EF007246)

true

Suitable for distribution board installation (EF007262)

false

Suitable for intermediate mounting (EF007264)

false

Complete device in housing (EF007317)

false

H...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-10-8374/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.