

INDUSTRIAL COMPONENT DATA

T0-2-1/E/SVC(S)-RT 044973 Y7-44973 EATON ELECTRIC Panic switches, 3 pole, 20 A, Padlocking feature SVC, fron..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-1/E/SVC(S)-RT



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-1/E/SVC(S)-RT
Catalog number	Y7-44973
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-3C96A3A49F
Generated	2026-08-01

Product Overview

Panic switches, 3 pole, 20 A, Padlocking feature SVC, front plate 0-1, 90 °, maintained, flush mounting, P
Panic Switch 3 Pole 20 A Padlock Lock SVC Plate
Panic switches, T0, 20 A, flush mounting, 3 pole, with red thumb grip and yellow front plate, Padlocking feature SVC
Panic switch, Product range: Switch with locking mechanism, Part group reference: T0, Stop Function: Emergency switching off function, with red thumb grip and yellow front plate, 3 pole, locking arrangement: Padlocking feature SVC,
Notes: Lockable with max. 3 padlocks., If the locking slide is interlocked with lock in position 1 the switch can be switched off but not on again without removing the lock., Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, front plate: 0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW , Rated uninterrupted current: Iu = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Panic switch Catalog Number 044973 Model Code T0-2-1/E/SVC(S)-RT EAN 4015080449737 Product Length/Depth 173 mm Product Height 73 mm Product Width 49 mm Product Weight 0.23 kg
Certifications IEC/EN 60947
IEC/EN 60947-3
IEC/EN 60204

VDE 0660

ETIM for 044973 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

20 A

Rated permanent current at AC-21, 400 V (EF009165)

20 A

Rated operation power at AC-3, 400 V (EF001364)

5.5 kW

Rated short-time withstand current Icw (EF007050)

0.32 kA

Rated operation power at AC-23, 400 V (EF007027)

5.5 kW

Switching power at 400 V (EF009166)

5.5 kW

Conditioned rated short-circuit current Iq (EF001444)

6 kA

Number of poles (EF001391)

3

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

No

Voltage release optional (EF007491)

No

Device construction (EF008240)

Built...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-1/E/SVC(S)-RT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.