

INDUSTRIAL COMPONENT DATA

T0-2-15114/Z 019877 Y7-19877 EATON ELECTRIC Step switches, Contacts: 4, 20 A, front plate: 0-1-1+2-2, 90 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15114/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15114/Z
Catalog number	Y7-19877
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-41EEFB5166
Generated	2026-08-03

Product Overview

Step switches, Contacts: 4, 20 A, front plate: 0-1-1+2-2, 90 °, maintained, rear mounting

Step switch 4 poles 20 A Indicator plate: 0-1-1+2-2 90

Eaton Moeller® series T0 Step switches, T0, 20 A, rear mounting, 2 contact unit(s), Contacts: 4, 90 °, maintained, With 0 (Off) position, 0-1-1+2-2, Design number 15114

Step switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-1+2-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 019877 Model Code T0-2-15114/Z EAN

4015080198772 Product Length/Depth 128 mm Product Height 48 mm Product Width 48 mm Product Weight 0.134 kg

Certifications CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

CSA Class No.: 3211-05

CSA File No.: 012528

VDE 0660

CE

IEC/EN 60947-3

IEC/EN 60947

UL File No.: E36332

IEC/EN 60204

CSA-C22.2 No. 94

UL

CSA

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 019877 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

1

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing material (EF00159...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15114/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.