

INDUSTRIAL COMPONENT DATA

T0-2-15313/E 011334 Y7-11334 EATON ELECTRIC On switches, Contacts: 3, 20 A, front plate: STOP START, 45 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15313/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15313/E
Catalog number	Y7-11334
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-542A21CA27
Generated	2026-08-04

Product Overview

On switches, Contacts: 3, 20 A, front plate: STOP

3-pole gear switch 20 A Indicator plate: STOP

Eaton Moeller® series T0 On switches, T0, 20 A, flush mounting, 2 contact unit(s), Contacts: 3, 45 °, momentary, Without 0 (Off) position, With spring-return to STOP, STOP

On switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: momentary, Without 0 (Off) position, With spring-return to STOP, 2 contact unit(s), Rated uninterrupted current: I_u = 20 A, front plate: STOP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 On switch Catalog Number 011334 Model Code T0-2-15313/E EAN

4015080113348 Product Length/Depth 86 mm Product Height 48 mm Product Width 48 mm Product Weight 0.108 kg

Certifications CSA Class No.: 3211-05

UL Category Control No.: NLRV

UL 60947-4-1

CE

CSA File No.: 012528

IEC/EN 60947-3

VDE 0660

IEC/EN 60204

CSA-C22.2 No. 94

UL

CSA

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 011334 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

3

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

2

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15313/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.