

INDUSTRIAL COMPONENT DATA

T0-2-15435/IVS 003195 Y7-3195 EATON ELECTRIC

Changeoverswitches, Contacts: 4, With spring-return from HAND, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15435/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15435/IVS
Catalog number	Y7-3195
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-3CA5CDACAB
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 4, With spring-return from HAND, 20 A, front plate: HAND>0-AUTO, 45 °, momentary/maintained, service distribution board mounting

4 Pole Switch With Return From Hand 20 To Plate

Eaton Moeller® series T0 Changeover switches, T0, 20 A, service distribution board mounting, 2 contact unit(s), Contacts: 4, With spring-return from HAND, 45 °, momentary/maintained, HAND>0-AUTO, Design number 15435

Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Spring-return: With spring-return from HAND, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to 0, 2 contact unit(s), Rated uninterrupted current: I_u = 20 A, front plate: HAND>0-AUTO

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 003195 Model Code T0-2-15435/IVS EAN 4015080031956 Product Length/Depth 92 mm Product Height 55 mm Product Width 54 mm Product Weight 0.12 kg
Certifications CSA

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

IEC/EN 60204

CSA-C22.2 No. 94

UL

UL File No.: E36332

CE

UL Category Control No.: NLRV

IEC/EN 60947-3

CSA Class No.: 3211-05

IEC/EN 60947

VDE 0660 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 003195 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

4

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15435/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.