

## INDUSTRIAL COMPONENT DATA

# T0-2-15435/Z 003196 Y7-3196 EATON ELECTRIC

## Changeoverswitches, Contacts: 4, With spring-return from HAND, 20..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15435/Z



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-2-15435/Z    |
| Catalog number  | Y7-3196         |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-600C42278B   |
| Generated       | 2026-08-05      |

### Product Overview

Changeoverswitches, Contacts: 4, With spring-return from HAND, 20 A, front plate: HAND>0-AUTO, 45 °, momentary/maintained, rear mounting

4 Pole Switch With Return From Hand 20 To Plate

Eaton Moeller® series T0 Changeover switches, T0, 20 A, rear mounting, 2 contact unit(s), Contacts: 4, With spring-return from HAND, 45°, momentary/maintained, With 0 (Off) position, With spring-return to 0, HAND>0-AUTO, Design no. 15435 Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Spring-return: With spring-return from HAND, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to 0, 2 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: HAND>0-AUTO

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

### Additional Product Information

## General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 003196 Model Code T0-2-15435/Z EAN 4015080031963 Product Length/Depth 128 mm Product Height 48 mm Product Width 48 mm Product Weight 0.134 kg Certifications CSA-C22.2 No. 60947-4-1-14

UL  
UL 60947-4-1  
CE  
CSA  
CSA File No.: 012528  
UL Category Control No.: NLRV  
CSA Class No.: 3211-05  
IEC/EN 60947-3  
CSA-C22.2 No. 94  
IEC/EN 60204  
IEC/EN 60947  
UL File No.: E36332  
VDE 0660 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second  
ETIM for 003196 Low-voltage industrial controls and switchgear (EC002611)  
Feature Name  
Feature Value  
Type of switch (EF003496)  
Reverser  
Number of poles (EF001391)  
2  
Max. rated operation voltage Ue AC (EF007355)  
690 V  
Rated permanent current Iu (EF001389)  
20 A  
Number of switch positions (EF000231)  
3  
With zero (off) position (EF001416)  
Yes  
With retraction in 0-position (EF002428)  
Yes  
Device construction (EF008240)  
Built-in device  
Width in number of modular spacings (EF002950)  
0  
Suitable for floor mounting (EF007243)  
Yes  
Suitable for front mounting (EF007246)  
No  
Suitable for distribution board installation (EF007262)  
No  
Suitable for intermediate mounting (EF007264)  
Yes  
Complete device in housing (EF007317)  
No  
Type of control element (EF006976)  
Toggle  
Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15435/Z with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.