

INDUSTRIAL COMPONENT DATA

T0-2-15452/XZ 011404 Y7-11404 EATON ELECTRIC

Changeover switch, 2p, Ie 12A, 90°, maintained, replacement swi..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15452/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15452/XZ
Catalog number	Y7-11404
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-A445066EBA
Generated	2026-08-03

Product Overview

Changeover switch, 2p, Ie=12A, 90°, maintained, replacement switch, base fixing

Switch 2-pole switch 20 A Indicator plate: Hand-AUTO 90°

Control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 4, Design: rear mounting, Basic switch, Switching angle: 90 °, 2 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: HAND-AUTO

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Changeover switch, 2p, Ie=12A, 90°, maintained, replacement switch, base fixingControl switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 4, Design: rear mounting, Basic switch, Switching angle: 90 °, 2 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: HAND-AUTODelivery program

Product rangeControl switchesPart group referenceT0Contacts4Designrear mounting

Basic switchContact sequenceSwitching angle90 °Design number15452Front plate no.front plateHAND-AUTOMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]5.5 kWRated uninterrupted current [Iu]20 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units2 contact unit(s)Technical data GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40
°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock
resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V
ACElectrical characteristicsRated uninterrupted current [Iu]20 AElectrical characteristicsNote on rated uninterrupted current
!uRated uninterrupted current Iuis specifi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15452/XZ with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.