

INDUSTRIAL COMPONENT DATA

T0-2-15503/XZ 011445 Y7-11445 EATON ELECTRIC Control switch, 1p, Ie 12A, 60°, maintained, replacement switch..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15503/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15503/XZ
Catalog number	Y7-11445
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-9665F628A5
Generated	2026-08-03

Product Overview

Control switch, 1p, Ie=12A, 60°, maintained, replacement switch, base fixing

Control switch 4 poles 20 A Indicator plate: Auto-Auf-Aus-Zu

Control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 4, Design: rear mounting, Basic switch, Switching angle: 60 °, 2 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: Auto-Auf-Aus-Zu

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Control switch, 1p, Ie=12A, 60°, maintained, replacement switch, base fixingControl switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 4, Design: rear mounting, Basic switch, Switching angle: 60 °, 2 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: Auto-Auf-Aus-ZuDelivery program

Product rangeControl switchesPart group referenceT0Contacts4Designrear mounting

Basic switchContact sequenceSwitching angle60 °Design number15503Front plate no.front plateAuto-Auf-Aus-ZuMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]5.5 kWRated uninterrupted current [Iu]20 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units2 contact unit(s)Technical data GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40

°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [U_{imp}] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [U_e] 690 V AC Electrical characteristics Rated uninterrupted current [I_u] 20 A Electrical characteristics Note on rated uninterrupted current I_u Rated uninterrupted current I_u...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15503/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.