

INDUSTRIAL COMPONENT DATA

T0-2-15907/I1 207095 Y7-207095 EATON ELECTRIC Changeoverswitches, Contacts: 4, With spring-return from START..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15907/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15907/I1
Catalog number	Y7-207095
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-0FA0CFDED4
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 4, With spring-return from START, 20 A, front plate: AUTO-0-HAND

T0-2-15907/I1

Eaton Moeller® series T0 Changeover switches, T0, 20 A, surface mounting, 2 contact unit(s), Contacts: 4, With spring-return from START, 45 °, momentary/maintained, AUTO-0-HAND

Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Spring-return: With spring-return from START, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to MANUAL, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: AUTO-0-HAND

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 207095 Model Code T0-2-15907/I1 EAN 4015082070953 Product Length/Depth 137 mm Product Height 102 mm Product Width 80 mm Product Weight 0.264 kg

Certifications IEC/EN 60204

IEC/EN 60947-3

IEC/EN 60947

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 207095 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

0

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

20 A

Number of switch positions (EF000231)

4

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Surface mounted device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15907/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.