

INDUSTRIAL COMPONENT DATA

T0-2-15907/I1/SVA(C,E,G-J) 207096 Y7-207096 EATON ELECTRIC Changeoverswitches, 4 pole, 20 A, Cylinder lock S..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15907/I1/SVA(C,E,G-J)



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15907/I1/SVA(C,E,G-J)
Catalog number	Y7-207096
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-49527F8D6A
Generated	2026-08-03

Product Overview

Changeoverswitches, 4 pole, 20 A, Cylinder lock SVA, front plate AUTO-0-HAND

T0-2-15907/I1/SVA(C,E,G-J)

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, surface mounting, 4 pole, with black thumb grip and front plate, Cylinder lock SVA

Changeover switch, Product range: Switch with locking mechanism, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, with two keys, 4 pole, Cylinder lock SVA, Locking facility: Lockable in position 0 with cover interlock, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: momentary/maintained, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A, Notes: If the key is withdrawn in HAND position, START can be actuated without the key, but not 0., front plate: AUTO-0-HAND

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 207096 Model Code

T0-2-15907/I1/SVA(C,E,G-J) EAN 4015082070960 Product Length/Depth 137 mm Product Height 102 mm Product Width 80 mm Product Weight 0.408 kg Certifications IEC/EN 60947

IEC/EN 60947-3

VDE 0660

IEC/EN 60204

ETIM for 207096 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

4

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

4

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Surface mounted device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15907/I1/SVA(C,E,G-J) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.