

INDUSTRIAL COMPONENT DATA

T0-2-15907/XZ 011478 Y7-11478 EATON ELECTRIC Contacts: 4, 20 A, 45 °, momentary/maintained, rear mounting, B..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15907/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15907/XZ
Catalog number	Y7-11478
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-DAD3D88D79
Generated	2026-08-03

Product Overview

Contacts: 4, 20 A, 45 °, momentary/maintained, rear mounting, Basic switch

4-Pole Switch Switch With Return From START 20 To Board

T0, 20 A, rear mounting, Basic switch, 2 contact unit(s), Contacts: 4, 45 °, momentary/maintained, design no. 15907

Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 4, Design: rear mounting, Basic switch, Switching angle: 45 °, Switching performance: momentary/maintained, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

T0, 20 A, rear mounting, Basic switch, 2 contact unit(s), Contacts: 4, 45 °, momentary/maintained, design no.

15907Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 4, Design: rear mounting, Basic switch, Switching angle: 45 °, Switching performance: momentary/maintained, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A

Delivery program

Product rangeControl switchesPart group referenceT0Contacts4Designrear mounting

Basic switchContact sequenceSwitching angle45 °Switching performancemomentary/maintainedDesign number15907Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]5.5 kWRated uninterrupted current [I_u]20 ANote on rated uninterrupted current !uRated uninterrupted current I_{uis} specified for max. cross-section.Number of contact units2 contact

unit(s) Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40

°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock

resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V

AC Electrical characteristics Rated uninterrupted current [Iu] 20 A Electrical characterist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15907/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.