

INDUSTRIAL COMPONENT DATA

T0-2-8425/Z 011828 Y7-11828 EATON ELECTRIC Auxiliary winding switch, Contacts: 3, 20 A, front plate: 0-1 STA..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-8425/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-8425/Z
Catalog number	Y7-11828
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-C3ABB040B2
Generated	2026-08-05

Product Overview

Auxiliary winding switch, Contacts: 3, 20 A, front plate: 0-1

Auxiliary winding switch 3 poles 20 A Indicator plate:

Auxiliary winding switch, T0, 20 A, rear mounting, 2 contact unit(s), Contacts: 3, 45 °, maintained, With 0 (Off) position, With spring-return to 1, 0-1

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, With spring-return to 1, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Auxiliary winding switch, T0, 20 A, rear mounting, 2 contact unit(s), Contacts: 3, 45 °, maintained, With 0 (Off) position, With spring-return to 1, 0-1Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, With spring-return to 1, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 0-1Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and

front plate, Contacts: 3, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, With spring-return to 1, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 0-1

General specifications Product name Eaton Moeller® series T0 Auxiliary winding switch Part no. T0-2-8425/ZEAN4015080118282 Product Length/Depth 128 millimetre Product height 48 millimetre Product width 48 millimetre Product weight 0.134 kilogram Certifications UL Category Control No.: NLRV

CE

CSA-C22.2 No. 94

IEC/EN 60947-3

CSA File No.: 012528

CSA

UL File No.: E36332

UL 60947-4-1

UL

VDE 0660

IE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-8425/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.