

INDUSTRIAL COMPONENT DATA

T0-2-SOND*/EZ/OFS 908033 Y7-908033 EATON ELECTRIC IAB & ICD Switching Devices

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-SOND*/EZ/OFS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-SOND*/EZ/OFS
Catalog number	Y7-908033
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-3145D3A074
Generated	2026-08-02

Product Overview

IAB & ICD Switching Devices
T0-2-SOND*/EZ/OFS
ROTARY SWIT. T-SOND/EZ,20A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

Delivery program

Product rangeNon-standard switchPart group referenceT0Notescustomized version according to formNon-standard
orderDesign number knownDesigncentre mountingMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]5.5 kWRated uninterrupted
current [Iu]20 ANote on rated uninterrupted current IuRated uninterrupted current Iuis specified for max.

cross-section.Number of contact units2 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40

°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock

resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V

ACElectrical characteristicsRated uninterrupted current [Iu]20 AElectrical characteristicsNote on rated uninterrupted current

!uRated uninterrupted current Iuis specified for max. cross-section.Load rating with intermittent operation, class 12AB 25 %

DF2 x IeLoad rating with intermittent operation, class 12AB 40 % DF1.6 x IeLoad rating with intermittent operation, class

12AB 60 % DF1.3 x IeShort-circuit ratingFuse20 A gG/gLRated short-time withstand current (1 s current) [Icw]320
ArmsNote on rated short-time withstand current IcwCurrent for a time of 1 secondRated conditional short-circuit cur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-SOND*/EZ/OFS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.