

INDUSTRIAL COMPONENT DATA

T0-3-123/Z 012280 Y7-12280 EATON ELECTRIC Reversing switches, Contacts: 6, 20 A, front plate: 2-0-1, 90 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-123/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-123/Z
Catalog number	Y7-12280
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C9C144C45C
Generated	2026-08-02

Product Overview

Reversing switches, Contacts: 6, 20 A, front plate: 2-0-1, 90 °, maintained, rear mounting, SOND 30

Inverter switch. 6 poles. 20 A. Indicator plate: 2-0-1. 90 °.

Eaton Moeller® series T0 Reversing switches, T0, 20 A, rear mounting, 3 contact unit(s), Contacts: 6, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 30, Design number 123

Reversing switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 30, Contacts: 6, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Reversing switch

Catalog Number 012280

Model Code T0-3-123/Z

EAN 4015080122807

Product Length/Depth 137 mm

Product Height 48 mm

Product Width 48 mm

Product Weight 0.163 kg

Certifications IEC/EN 60947-3

UL 60947-4-1

UL File No.: E36332

IEC/EN 60947

UL

CSA Class No.: 3211-05

UL Category Control No.: NLRV

CSA-C22.2 No. 94

CSA File No.: 012528

CSA

CE

VDE 0660

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

Features & Functions

Features Version as reversing switch

Fitted with: Black thumb grip and front plate

Inscription 2-0-1

Number of poles 3

General

Degree of protection NEMA 12

Degree of protection (front side) IP65

Lifespan, mechanical 400,000 Operations

Mounting method Rear mounting

Mounting position As required

Number of contact units 3

Operating frequency 1200 Operations/h

Overvoltage category III

Pollution degree 3

Product Category Control switches

Rated impulse withstand voltage (Uimp) 6000 V AC

Safe isolation 440 V AC, Between the contacts, According to EN 61140

Safety parameter (EN ISO 13849-1) B10d values as per EN ISO 13849-1, table C.1

Shock resistance 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms

Suitable for Intermediate mounting

Ground mounting

Branch circuits, suitable as motor disconnect, (UL/CSA)

Switching angle 60 °

Type Reversing switch

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temperature - max 50 °C

Ambient operating tem...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-123/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.