

INDUSTRIAL COMPONENT DATA

T0-3-15393/EZ 060214 Y7-60214 EATON ELECTRIC Universal control switches, Contacts: 6, 20 A, front plate: 2 0..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15393/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15393/EZ
Catalog number	Y7-60214
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-698C3DEBF5
Generated	2026-08-05

Product Overview

Universal control switches, Contacts: 6, 20 A, front plate: 2>0-1, 45 °, momentary/maintained, centre mounting

Universal Control Switch 6-pole 20 A Indicator plate: 2>0-1

Eaton Moeller® series T0 Universal control switches, T0, 20 A, center mounting, 3 contact unit(s), Contacts: 6, 45 °, momentary/maintained, With 0 (Off) position, With spring-return to 0, 2>0-1, Design number 15393

Universal control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to 0, 3 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 2>0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Universal control switch Catalog Number 060214 Model Code T0-3-15393/EZ

EAN 4015080602149 Product Length/Depth 115 mm Product Height 48 mm Product Width 48 mm Product Weight 0.153 kg

Certifications UL 60947-4-1

UL File No.: E36332

IEC/EN 60204

VDE 0660

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

UL Category Control No.: NLRV

CSA

UL

CSA File No.: 012528

IEC/EN 60947

CE

CSA Class No.: 3211-05

CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 060214 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Group switch

Number of poles (EF001391)

0

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15393/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.