

INDUSTRIAL COMPONENT DATA

T0-3-15433/Z 057840 Y7-57840 EATON ELECTRIC Changeoverswitches, Contacts: 6, 20 A, front plate: HAND-0-AUTO,..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15433/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15433/Z
Catalog number	Y7-57840
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-BAA1A428DA
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 6, 20 A, front plate: HAND-0-AUTO, 45 °, maintained, rear mounting

Switch 6-pole switch 20 A Indicator plate: Hand-0-AUTO 45

Eaton Moeller® series T0 Changeoverswitches, T0, 20 A, rear mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, With 0 (Off) position, HAND-0-AUTO, Design number 15433

Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 3 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: HAND-0-AUTO

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Changeover switch Catalog Number 057840 Model Code T0-3-15433/Z EAN 4015080578406 Product Length/Depth 137 mm Product Height 48 mm Product Width 48 mm Product Weight 0.163 kg

Certifications IEC/EN 60947-3

UL Category Control No.: NLRV

CSA Class No.: 3211-05

VDE 0660

CSA-C22.2 No. 94

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

UL

IEC/EN 60204

CSA

CE

CSA File No.: 012528

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 057840 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

3

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15433/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.