

INDUSTRIAL COMPONENT DATA

T0-3-8426/I1 222672 Y7-222672 EATON ELECTRIC Auxiliary winding switch, Contacts: 6, 20 A, front plate: 2-STA..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-8426/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-8426/I1
Catalog number	Y7-222672
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-4C244F907A
Generated	2026-08-03

Product Overview

Auxiliary winding switch, Contacts: 6, 20 A, front plate: 2-START>0

T0-3-8426/I1

Eaton Moeller® series T0 Auxiliary winding switch, T0, 20 A, surface mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, With 0 (Off) position, with spring-return from both directions to 0, 2-START>0

Auxiliary winding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, with spring-return from both directions to 0, 3 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 2-START>0

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Auxiliary winding switch Catalog Number 222672 Model Code T0-3-8426/I1 EAN 4015082226725 Product Length/Depth 137 mm Product Height 122 mm Product Width 80 mm Product Weight 0.288 kg

Certifications EN 60947

EN 60204

IEC 60947

VDE

IEC/EN 60947-3

IEC/EN 60204

IEC/EN 60947

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 222672 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

2

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

20 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Surface mounted device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-8426/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.