

INDUSTRIAL COMPONENT DATA

T0-3-8901/EA/SVB 231932 Y7-231932 EATON ELECTRIC Main switch, 3 pole + N + 1 N/O + 1 N/C, 20 A, Emergency-St..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-8901/EA/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-8901/EA/SVB
Catalog number	Y7-231932
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-51E77C1930
Generated	2026-08-04

Product Overview

Main switch, 3 pole + N + 1 N/O + 1 N/C, 20 A, Emergency-Stop function, 90 °, Lockable in the 0 (Off) position, flush mounting

T0-3-8901/EA/SVB

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T0, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 3 pole + N, Locking facility: Lockable in the 0 (Off) position, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Main switch Catalog Number 231932 Model Code T0-3-8901/EA/SVB EAN 4015082319328 Product Length/Depth 120 mm Product Height 74 mm Product Width 65 mm Product Weight 0.142 kg

Compliances CE Marked Certifications IEC 60947

CSA Std. C22.2 No. 14-05

EN 60947-3

UL 508

VDE

CSA
IEC/EN 60204
UL File No.: E36332
IEC/EN 60947-3
UL
CE
CSA-C22.2 No. 94
CSA Class No.: 3211-05
CSA-C22.2 No. 60947-4-1-14
VDE 0660
CSA File No.: 012528
IEC/EN 60947
UL 60947-4-1
UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 231932 Low-voltage industrial controls and switchgear (EC000216)
Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
Yes
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
20 A
Rated permanent current at AC-23, 400 V (EF011777)
13.3 A
Rated permanent current at AC-21, 400 V (EF009165)
20 A
Rated operation power at AC-3, 400 V (EF001364)
5.5 kW
Rated short-time withstand current I_{cw} (EF007050)
0.32 kA
Rated operation power at AC-23, 400 V (EF007027)
5.5 kW
Switching power at 400 V (EF009166)
5.5 kW

Conditioned rated short-circuit current I_q (EF001444)

6 kA

N...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-8901/EA/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.