

INDUSTRIAL COMPONENT DATA

T0-3-SOND*/E 907767 Y7-907767 EATON ELECTRIC

Non-standard switch, T0, 20 A, flush mounting, 3 contact unit(s)

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-SOND*/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-SOND*/E
Catalog number	Y7-907767
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-475762CF50
Generated	2026-08-03

Product Overview

Non-standard switch, T0, 20 A, flush mounting, 3 contact unit(s)

T0-3-SOND*/E

Eaton Moeller® series T0 Non-standard switch, T0, 20 A, flush mounting, 3 contact unit(s)

Non-standard switch, Product range: Non-standard switch, Part group reference: T0, Notes: customized version according to form, Degree of Protection: Front IP65, Design: flush mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Non-standard switch Catalog Number 907767 Model Code T0-3-SOND*/E Product Length/Depth 95 mm Product Height 48 mm Product Width 48 mm Product Weight 0.121 kg Certifications VDE 0660

IEC/EN 60204

IEC/EN 60947-3

IEC/EN 60947

ETIM for 907767 Low-voltage industrial controls and switchgear (EC000216)

Feature Name	Feature Value
Version as main switch (EF006981)	No
Version as maintenance-/service switch (EF006986)	No
Version as safety switch (EF006985)	No
Version as emergency stop installation (EF006959)	No
Version as reversing switch (EF009408)	No
Number of switches (EF005586)	1
Max. rated operation voltage Ue AC (EF007355)	690 V
Rated operating voltage (EF001435)	690 V
Rated permanent current Iu (EF001389)	20 A
Rated permanent current at AC-23, 400 V (EF011777)	13.3 A
Rated permanent current at AC-21, 400 V (EF009165)	20 A
Rated operation power at AC-3, 400 V (EF001364)	5.5 kW
Rated short-time withstand current Icw (EF007050)	0.32 kA
Rated operation power at AC-23, 400 V (EF007027)	5.5 kW
Switching power at 400 V (EF009166)	5.5 kW
Conditioned rated short-circuit current Iq (EF001444)	6 kA
Number of auxiliary contacts as normally closed contact (EF001377)	0
Number of auxiliary contacts as normally open contact (EF001376)	0
Number of auxiliary contacts as change-over contact (EF003531)	0
Motor drive optional (EF007386)	No
Motor drive integrated (EF006697)	No
Voltage release optional (EF007491)	No
Device construction (EF00...	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-SOND*/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.