

INDUSTRIAL COMPONENT DATA

T0-3-SOND*/V/SVB-SW 908056 Y7-908056 EATON ELECTRIC

Non-standard switch, T0, 20 A, rear mounting, 3 contact ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-SOND*/V/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-SOND*/V/SVB-SW
Catalog number	Y7-908056
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-D529973EC6
Generated	2026-08-05

Product Overview

Non-standard switch, T0, 20 A, rear mounting, 3 contact unit(s)

T0-3-SOND*/V/SVB-SW

Eaton Moeller® series T0 Non-standard switch, T0, 20 A, rear mounting, 3 contact unit(s), STOP function, With black rotary handle and locking ring

Non-standard switch, Product range: Non-standard switch, Part group reference: T0, Stop Function: STOP function, With black rotary handle and locking ring, Notes: customized version according to form, Degree of Protection: Front IP65, Design: rear mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Non-standard switch Catalog Number 908056 Model Code

T0-3-SOND*/V/SVB-SW Product Length/Depth 137 mm Product Height 74 mm Product Width 65 mm Product Weight 0.158 kg Certifications IEC/EN 60947-3

IEC/EN 60204

IEC/EN 60947

VDE 0660

ETIM for 908056 Low-voltage industrial controls and switchgear (EC000216)

Feature Name	
Feature Value	
Version as main switch (EF006981)	
Yes	
Version as maintenance-/service switch (EF006986)	
Yes	
Version as safety switch (EF006985)	
No	
Version as emergency stop installation (EF006959)	
No	
Version as reversing switch (EF009408)	
No	
Number of switches (EF005586)	
1	
Rated operating voltage (EF001435)	
690 V	
Rated permanent current I _u (EF001389)	
20 A	
Rated permanent current at AC-23, 400 V (EF011777)	
13.3 A	
Rated permanent current at AC-21, 400 V (EF009165)	
20 A	
Rated operation power at AC-3, 400 V (EF001364)	
5.5 kW	
Rated short-time withstand current I _{cw} (EF007050)	
0.32 kA	
Rated operation power at AC-23, 400 V (EF007027)	
5.5 kW	
Switching power at 400 V (EF009166)	
5.5 kW	
Conditioned rated short-circuit current I _q (EF001444)	
6 kA	
Number of auxiliary contacts as normally closed contact (EF001377)	
0	
Number of auxiliary contacts as normally open contact (EF001376)	
0	
Number of auxiliary contacts as change-over contact (EF003531)	
0	
Motor drive optional (EF007386)	
No	
Motor drive integrated (EF006697)	
No	
Voltage release optional (EF007491)	
No	
Device construction (EF008240)	
Built-in device fixed built-in techn...	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-SOND*/V/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.