

INDUSTRIAL COMPONENT DATA

T0-4-15602/I1 207134 Y7-207134 EATON ELECTRIC Coding switches, Contacts: 8, 20 A, Binary BCD code 0-9, front..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-15602/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-15602/I1
Catalog number	Y7-207134
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-FD2A698F8F
Generated	2026-08-05

Product Overview

Coding switches, Contacts: 8, 20 A, Binary BCD code 0-9, front plate: 0-9, 30 °, maintained, surface mounting
T0-4-15602/I1

Eaton Moeller® series T0 Coding switches, T0, 20 A, surface mounting, 4 contact unit(s), Contacts: 8, 30 °, maintained, With 0 (Off) position, 0-9, Design number 15602

Coding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: IP65, Design: surface mounting, switching function: Binary BCD code 0-9, Switching angle: 30 °, Switching performance: maintained, With 0 (Off) position, 4 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 0-9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Coding switch Catalog Number 207134 Model Code T0-4-15602/I1 EAN 4015082071349 Product Length/Depth 137 mm Product Height 122 mm Product Width 80 mm Product Weight 0.36 kg

Certifications IEC/EN 60204

IEC/EN 60947-3

VDE 0660

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 207134 Low-voltage industrial controls and switchgear (EC002611)

Feature Name
Feature Value
Type of switch (EF003496)
Coding switch
Number of poles (EF001391)
0
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated permanent current Iu (EF001389)
20 A
Number of switch positions (EF000231)
10
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Device construction (EF008240)
Surface mounted device
Width in number of modular spacings (EF002950)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
Yes
Type of control element (EF006976)
Toggle
Front shield size (EF007176)
48x48 mm
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-15602/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.