

INDUSTRIAL COMPONENT DATA

T0-6-66/E 015487 Y7-15487 EATON ELECTRIC Reversing multi-speed switches, Contacts: 12, 20 A, One tapped wind..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-66/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-66/E
Catalog number	Y7-15487
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-FCCD798294
Generated	2026-08-01

Product Overview

Reversing multi-speed switches, Contacts: 12, 20 A, One tapped winding, 2 speeds, front plate: 2-1-0-1-2, 60 °, maintained, flush mounting

Multi-speed switch with reversing 12 poles 20 A 1 winding

Eaton Moeller® series T0 Reversing multi-speed switches, T0, 20 A, flush mounting, 6 contact unit(s), Contacts: 12, 60 °, maintained, With 0 (Off) position, 2-1-0-1-2, Design number 66

Reversing multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 12, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Reversing multi-speed switch Catalog Number 015487 Model Code T0-6-66/E
EAN 4015080154877 Product Length/Depth 124 mm Product Height 48 mm Product Width 48 mm Product Weight 0.16 kg
Certifications CSA File No.: 012528
CSA-C22.2 No. 94
IEC/EN 60947

CSA Class No.: 3211-05

CSA

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

UL

UL Category Control No.: NLRV

UL File No.: E36332

VDE 0660

CE

IEC/EN 60204

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 015487 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reversing Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-66/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.