

## INDUSTRIAL COMPONENT DATA

**T3-1-15322/XZ 016469 Y7-16469 EATON ELECTRIC Control switch, 2p, Ie 25A, 45°, momentary, replacement switch,..**

Brand: EATON - MOELLER | Manufacturer Part Number: T3-1-15322/XZ



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-1-15322/XZ   |
| Catalog number  | Y7-16469        |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-4B6C42393B   |
| Generated       | 2026-08-05      |

**Product Overview**

Control switch, 2p, Ie=25A, 45°, momentary, replacement switch, base fixing

Control switch 2 poles 32 A Indicator plate: I

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Disconnectors and Cam Switches

**Additional Product Information**

Control switch, 2p, Ie=25A, 45°, momentary, replacement switch, base fixingControl switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 2, Design: rear mounting, Basic switch, Switching angle: 45 °, 1 contact unit(s), Rated uninterrupted current: Iu= 32 ADelivery program

Product rangeControl switchesPart group referenceT3Contacts2Designrear mounting

Basic switchContact sequenceSwitching angle45 °Design number15322Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [Iu]32 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units1 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40 °COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V ACElectrical characteristicsRated uninterrupted current [Iu]32 AElectrical characteristicsNote on rated uninterrupted current

!uRated uninterrupted current Iuis specified for max. cross-section.Load rating with interm...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-1-15322/XZ with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.