

INDUSTRIAL COMPONENT DATA

T3-1-15341/E 016480 Y7-16480 EATON ELECTRIC On switches, Contacts: 1, 32 A, front plate: START STOP, 45 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-1-15341/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-1-15341/E
Catalog number	Y7-16480
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-6C0EB0D2EE
Generated	2026-08-01

Product Overview

On switches, Contacts: 1, 32 A, front plate: START

1-pole 32 A gear switch Indicator plate: START

Eaton Moeller® series T3 On switches, T3, 32 A, flush mounting, 1 contact unit(s), Contacts: 1, 45 °, momentary, With 0 (Off) position, With spring-return to START, START

On switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 1, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: momentary, With 0 (Off) position, With spring-return to START, 1 contact unit(s), Rated uninterrupted current: I_u = 32 A, front plate: START

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 On switch Catalog Number 016480 Model Code T3-1-15341/E EAN

4015080164807 Product Length/Depth 79 mm Product Height 54 mm Product Width 61 mm Product Weight 0.11 kg

Certifications IEC/EN 60204

CSA File No.: 012528

CSA

UL Category Control No.: NLRV

UL File No.: E36332

CE

VDE 0660

CSA-C22.2 No. 94

UL

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

IEC/EN 60947

IEC/EN 60947-3 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 016480 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

32 A

Number of switch positions (EF000231)

2

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-1-15341/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.