

INDUSTRIAL COMPONENT DATA

T3-1-15511/XZ 016581 Y7-16581 EATON ELECTRIC Contacts: 2, 32 A, 90 °, rear mounting, Basic switch

Brand: EATON - MOELLER | Manufacturer Part Number: T3-1-15511/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-1-15511/XZ
Catalog number	Y7-16581
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-25321FFAC8
Generated	2026-08-02

Product Overview

Contacts: 2, 32 A, 90 °, rear mounting, Basic switch

ON-OFF pushbutton switch 2-pole 32 A Indicator plate: 0-1

Control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 2, Design: rear mounting, Basic switch, Switching angle: 90 °, 1 contact unit(s), Rated uninterrupted current: I_u= 32 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Contacts: 2, 32 A, 90 °, rear mounting, Basic switchControl switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 2, Design: rear mounting, Basic switch, Switching angle: 90 °, 1 contact unit(s), Rated uninterrupted current: I_u= 32 A
Delivery program

Product rangeControl switchesPart group referenceT3Contacts2Designrear mounting

Basic switchContact sequenceSwitching angle90 °Design number15511Front plate no.Motor rating AC-23A, 50 - 60 Hz
[P]400 V [P]15 kWRated uninterrupted current [I_u]32 ANote on rated uninterrupted current !uRated uninterrupted current
I_uis specified for max. cross-section.Number of contact units1 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40

°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [U_{imp}] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [U_e] 690 V AC Electrical characteristics Rated uninterrupted current [I_u] 32 A Electrical characteristics Note on rated uninterrupted current I_u Rated uninterrupted current I_u is specified for max. cross-section. Load rating with intermittent operation, class...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-1-15511/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.