

INDUSTRIAL COMPONENT DATA

T3-2-15114/E 085593 Y7-85593 EATON ELECTRIC Step switches, Contacts: 4, 32 A, front plate: 0-1-1+2-2, 90 °, ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-15114/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-15114/E
Catalog number	Y7-85593
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-1C465B689A
Generated	2026-08-01

Product Overview

Step switches, Contacts: 4, 32 A, front plate: 0-1-1+2-2, 90 °, maintained, flush mounting

Step switch 4-pole 32 A Indicator plate: 0-1-1+2-2 90

Eaton Moeller® series T3 Step switches, T3, 32 A, flush mounting, 2 contact unit(s), Contacts: 4, 90 °, maintained, With 0 (Off) position, 0-1-1+2-2, Design number 15114

Step switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-1-1+2-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 085593 Model Code T3-2-15114/E EAN 4015080855934 Product Length/Depth 91 mm Product Height 54 mm Product Width 61 mm Product Weight 0.172 kg

Certifications CSA

CSA Class No.: 3211-05

CSA File No.: 012528

CSA-C22.2 No. 94

IEC/EN 60204

CE

UL 60947-4-1

IEC/EN 60947-3

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332

UL Category Control No.: NLRV

VDE 0660

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 085593 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

On/Off switch

Number of poles (EF001391)

2

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-15114/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.