

## INDUSTRIAL COMPONENT DATA

# T3-2-15403/E 052373 Y7-52373 EATON ELECTRIC ON-OFF switches, Contacts: 3, 32 A, front plate: 0-1, 45 °, main..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-15403/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-2-15403/E    |
| Catalog number  | Y7-52373        |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-FB080F368F   |
| Generated       | 2026-08-03      |

## Product Overview

ON-OFF switches, Contacts: 3, 32 A, front plate: 0-1, 45 °, maintained, flush mounting

ON-OFF 3-pole disconnecter switch 32 A Indicator plate: 0-1 45

Eaton Moeller® series T3 ON-OFF switches, T3, 32 A, flush mounting, 2 contact unit(s), Contacts: 3, 45 °, maintained, With 0 (Off) position, 0-1, Design number 15403

On-Off switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 2 contact unit(s), Rated uninterrupted current: I<sub>u</sub>= 32 A, front plate: 0-1

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 On-off switch Catalog Number 052373 Model Code T3-2-15403/E EAN 4015080523734 Product Length/Depth 91 mm Product Height 54 mm Product Width 61 mm Product Weight 0.172 kg

Certifications CE

CSA

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

IEC/EN 60947

UL

CSA Class No.: 3211-05

UL Category Control No.: NLRV

CSA File No.: 012528

IEC/EN 60947-3

UL 60947-4-1

VDE 0660

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I<sub>cs</sub>) for a time of 1 second

ETIM for 052373 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

3

Max. rated operation voltage U<sub>e</sub> AC (EF007355)

690 V

Rated permanent current I<sub>n</sub> (EF001389)

32 A

Number of switch positions (EF000231)

2

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-15403/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.