

INDUSTRIAL COMPONENT DATA

T3-2-15435/I2 222758 Y7-222758 EATON ELECTRIC

Changeoverswitches, Contacts: 4, 32 A, front plate: HAND 0-AUT..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-15435/I2



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-15435/I2
Catalog number	Y7-222758
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-F54CCFADB8
Generated	2026-08-02

Product Overview

Changeoverswitches, Contacts: 4, 32 A, front plate: HAND>0-AUTO, 45 °, momentary/maintained, surface mounting
T3-2-15435/I2

Eaton Moeller® series T3 Changeover switches, T3, 32 A, surface mounting, 2 contact unit(s), Contacts: 4, 45 °, momentary/maintained, With 0 (Off) position, With spring-return to 0, HAND>0-AUTO, Design number 15435
Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 4, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to 0, 2 contact unit(s), Rated uninterrupted current: Iu= 32 A, front plate: HAND>0-AUTO

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 222758 Model Code T3-2-15435/I2 EAN 4015082227586 Product Length/Depth 181 mm Product Height 107 mm Product Width 100 mm Product Weight 0.364 kg
Certifications UL 60947-4-1
CE

CSA Class No.: 3211-07

IEC/EN 60947-3

IEC/EN 60947

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14

CSA File No.: 012528

UL File No.: E36332

UL Category Control No.: NLRV

VDE 0660

UL

CSA

CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 222758 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

32 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Device construction (EF008240)

Surface mounted device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-15435/I2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.