

## INDUSTRIAL COMPONENT DATA

# T3-2-15442/E 018116 Y7-18116 EATON ELECTRIC

## Changeoverswitches, Contacts: 4, 32 A, front plate: 1-2, 90 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-15442/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-2-15442/E    |
| Catalog number  | Y7-18116        |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-D97677832E   |
| Generated       | 2026-08-01      |

### Product Overview

Changeoverswitches, Contacts: 4, 32 A, front plate: 1-2, 90 °, maintained, flush mounting

Switch 4-pole 32 A Indicator plate: 1-2 90°

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, flush mounting, 2 contact unit(s), Contacts: 4, 90 °, maintained, Without 0 (Off) position, 1-2, Design number 15442

Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 4, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: maintained, Without 0 (Off) position, 2 contact unit(s), Rated uninterrupted current: Iu= 32 A, front plate: 1-2

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                  |
|--------------|--------------------------------------------------|
| Catalog path | EATON - MOELLER > Disconnectors and Cam Switches |
|--------------|--------------------------------------------------|

### Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 018116 Model Code T3-2-15442/E EAN 4015080181163 Product Length/Depth 91 mm Product Height 54 mm Product Width 61 mm Product Weight 0.172 kg

Certifications IEC/EN 60204

VDE 0660

UL

CSA

CSA Class No.: 3211-05

IEC/EN 60947-3

CE

CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947

CSA-C22.2 No. 94

UL 60947-4-1

UL Category Control No.: NLRV

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second  
ETIM for 018116 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Reverser

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

32 A

Number of switch positions (EF000231)

2

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / T3-2-15442/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.