

INDUSTRIAL COMPONENT DATA

T3-3-15423/I2 222868 Y7-222868 EATON ELECTRIC Industrial Automation Bussines and Industrial Control Devices ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-15423/I2



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-15423/I2
Catalog number	Y7-222868
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-0F85A4260B
Generated	2026-08-02

Product Overview

Industrial Automation Bussines and Industrial Control Devices Switching Devices

T3-3-15423/I2

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, surface mounting, 3 contact unit(s), Contacts: 6, 45 °, maintained, With 0 (Off) position, 2-0-1, Design number 15423

Changeover switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 6, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 222868 Model Code T3-3-15423/I2 EAN 4015082228682 Product Length/Depth 181 mm Product Height 127 mm Product Width 100 mm Product Weight 0.563 kg

Certifications CSA

UL 60947-4-1

UL

UL Category Control No.: NLRV

IEC/EN 60204

UL File No.: E36332

IEC/EN 60947-3

VDE 0660

CSA-C22.2 No. 94

CE

CSA File No.: 012528

CSA Class No.: 3211-07

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 222868 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

Yes

Housing materia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-15423/I2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.