

INDUSTRIAL COMPONENT DATA

T3-3-15443/XZ 018837 Y7-18837 EATON ELECTRIC

Changeover switch, 3p, Ie 25A, 1-2, 90°, maintained, replacement..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-3-15443/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-3-15443/XZ
Catalog number	Y7-18837
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-A85BB035A0
Generated	2026-08-03

Product Overview

Changeover switch, 3p, Ie=25A, 1-2, 90°, maintained, replacement switch, base fixing

Switch 3-pole switch 32 A Indicator plate: 1-2 90°

Changeoverswitches, T3, 32 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 6, 90 °, design no. 15443

Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 6, Design: rear mounting, Basic switch, Switching angle: 90 °, 3 contact unit(s), Rated uninterrupted current: Iu= 32 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Changeoverswitches, T3, 32 A, rear mounting, Basic switch, 3 contact unit(s), Contacts: 6, 90 °, design no.

15443Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204,

Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 6, Design: rear mounting, Basic switch, Switching angle: 90 °, 3 contact unit(s), Rated uninterrupted current: Iu= 32 A

Product rangeControl switchesPart group referenceT3Basic functionChangeoverswitchesContacts6Designrear mounting

Basic switchContact sequenceSwitching angle90 °Design number15443Front plate no.Motor rating AC-23A, 50 - 60 Hz
[P]400 V [P]15 kWRated uninterrupted current [Iu]32 ANote on rated uninterrupted current !uRated uninterrupted current
Iuis specified for max. cross-section.Number of contact units3 contact unit(s)Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open -25 - +50 °C Ambient temperature Enclosed -25 - +40

°C Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock

resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V

AC Electrical characteristics Rated uninterrupted current [Iu] 32 A Electrical characteristics Note on rated uninterrupted current

Iu Rated uninterrupt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-3-15443/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.