

## INDUSTRIAL COMPONENT DATA

# T3-4-15374/XZ 020179 Y7-20179 EATON ELECTRIC Control switch, 4p, Ie 25A, 20 1, 45°, momentary, replacement ..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-15374/XZ



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T3-4-15374/XZ   |
| Catalog number  | Y7-20179        |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-795A588209   |
| Generated       | 2026-08-03      |

## Product Overview

Control switch, 4p, Ie=25A, 2&gt;00

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog pathEATON - MOELLER &gt; Disconnectors and Cam Switches

## Additional Product Information

T3, 32 A, rear mounting, Basic switch, 4 contact unit(s), Contacts: 8, 45 °, design no. 15374Changeover switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, Contacts: 8, Design: rear mounting, Basic switch, Switching angle: 45 °, 4 contact unit(s), Rated uninterrupted current: Iu= 32 ADelivery program

Product rangeControl switchesPart group referenceT3Contacts8Designrear mounting

Basic switchContact sequenceSwitching angle45 °Design number15374Front plate no.Motor rating AC-23A, 50 - 60 Hz [P]400 V [P]15 kWRated uninterrupted current [Iu]32 ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact units4 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40

°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock

resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V

ACElectrical characteristicsRated uninterrupted current [Iu]32 AElectrical characteristicsNote on rated uninterrupted current

!uRated uninterrupted current Iuis specified for max. cross-section.Lo...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-15374/XZ with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.