

INDUSTRIAL COMPONENT DATA

T3-4-8902/Z 215225 Y7-215225 EATON ELECTRIC

Changeoverswitches, Contacts: 8, 32 A, front plate: Netz-0-Notst..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-4-8902/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-4-8902/Z
Catalog number	Y7-215225
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-8EDE798000
Generated	2026-08-05

Product Overview

Changeoverswitches, Contacts: 8, 32 A, front plate: Netz-0-Notstrom, 45 °, maintained, rear mounting
T3-4-8902/Z

Eaton Moeller® series T3 Changeoverswitches, T3, 32 A, rear mounting, 4 contact unit(s), Contacts: 8, 60 °, maintained, With 0 (Off) position, Netz-0-Notstrom, Design number 8902

Changeover switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: Netz-0-Notstrom, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Changeover switch Catalog Number 215225 Model Code T3-4-8902/Z EAN 4015082152253 Product Length/Depth 156 mm Product Height 54 mm Product Width 61 mm Product Weight 0.286 kg
Compliances CE Marked Certifications IEC 60947
EN 60947-3

UL 508

CSA Std. C22.2 No. 14-05

VDE

CSA File No.: 012528

UL Category Control No.: NLRV

CSA-C22.2 No. 60947-4-1-14

CE

CSA-C22.2 No. 94

CSA Class No.: 3211-05

CSA

IEC/EN 60947-3

UL File No.: E36332

VDE 0660

IEC/EN 60204

UL 60947-4-1

IEC/EN 60947

UL Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 215225 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

4

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

32 A

Rated operation current Ie at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mount...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-4-8902/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.