

INDUSTRIAL COMPONENT DATA

T5-4-SOND*/I5/SVB-SW 207535 Y7-207535 EATON ELECTRIC

Non-standard switch, T5, 100 A, surface mounting, 4 con..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-4-SOND*/I5/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T5-4-SOND*/I5/SVB-SW
Catalog number	Y7-207535
Category	Switch disconnecter
Minimum order	10 Pcs
Document ID	EO-028BA44947
Generated	2026-08-03

Product Overview

Non-standard switch, T5, 100 A, surface mounting, 4 contact unit(s)

T5-4-SOND*/I5/SVB-SW

Eaton Moeller® series T5 Non-standard switch, T5, 100 A, surface mounting, 4 contact unit(s), STOP function, With black rotary handle and locking ring

Non-standard switch, Product range: Non-standard switch, Part group reference: T5, Stop Function: STOP function, With black rotary handle and locking ring, Notes: customized version according to form, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: I_u = 100 A, 4 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5 Non-standard switch Catalog Number 207535 Model Code

T5-4-SOND*/I5/SVB-SW Product Length/Depth 280 mm Product Height 204 mm Product Width 200 mm Product Weight 2.038 kg Certifications VDE 0660

IEC/EN 60947

IEC/EN 60204

IEC/EN 60947-3

ETIM for 207535 Low-voltage industrial controls and switchgear (EC000216)

Feature Name
Feature Value
Version as main switch (EF006981)
Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
100 A
Rated permanent current at AC-23, 400 V (EF011777)
100 A
Rated permanent current at AC-21, 400 V (EF009165)
100 A
Rated operation power at AC-3, 400 V (EF001364)
30 kW
Rated short-time withstand current I_{cw} (EF007050)
1.7 kA
Rated operation power at AC-23, 400 V (EF007027)
55 kW
Switching power at 400 V (EF009166)
55 kW
Conditioned rated short-circuit current I_q (EF001444)
2 kA
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Motor drive optional (EF007386)
No
Motor drive integrated (EF006697)
No
Voltage release optional (EF007491)
No
Device construction (EF008240)
Complete device in housing
Suitable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-4-SOND*/I5/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.