

INDUSTRIAL COMPONENT DATA

T5-6-15168/EA/SVB 094894 Y7-94894 EATON ELECTRIC Main switch, 9-pole + 2 N/O + 1 N/C, 100 A, Emergency-Stop ..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-6-15168/EA/SVB



Manufacturer	EATON - MOELLER
MPN / Reference	T5-6-15168/EA/SVB
Catalog number	Y7-94894
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-88B2F33075
Generated	2026-08-05

Product Overview

Main switch, 9-pole + 2 N/O + 1 N/C, 100 A, Emergency-Stop function, 90 °, flush mounting

General Switch 9 poles + 1 NO + 1 NC 100 A 90° Mounting

Eaton Moeller® series T5 Main switch, T5, 100 A, flush mounting, 6 contact unit(s), 9-pole, 2 N/O, 1 N/C, Emergency switching off function, With red rotary handle and yellow locking ring

Main switch, Product range: Main switch, maintenance switch, Repair switch, Part group reference: T5, Stop Function: Emergency switching off function, With red rotary handle and yellow locking ring, 9-pole, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 55 kW, Rated uninterrupted current: Iu = 100 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T5 Main switch Catalog Number 094894 Model Code T5-6-15168/EA/SVB EAN 4015080948940 Product Length/Depth 206 mm Product Height 88 mm Product Width 88 mm Product Weight 1.245 kg

Certifications IEC/EN 60947

IEC/EN 60204

IEC/EN 60947-3

VDE 0660 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 094894 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes

Version as maintenance-/service switch (EF006986)

Yes

Version as safety switch (EF006985)

No

Version as emergency stop installation (EF006959)

Yes

Version as reversing switch (EF009408)

No

Number of switches (EF005586)

1

Max. rated operation voltage Ue AC (EF007355)

600 V

Rated operating voltage (EF001435)

690 V

Rated permanent current Iu (EF001389)

100 A

Rated permanent current at AC-21, 400 V (EF009165)

100 A

Rated operation power at AC-3, 400 V (EF001364)

30 kW

Rated short-time withstand current Icw (EF007050)

1.7 kA

Rated operation power at AC-23, 400 V (EF007027)

55 kW

Switching power at 400 V (EF009166)

55 kW

Conditioned rated short-circuit current Iq (EF001444)

2 kA

Number of poles (EF001391)

9

Number of auxiliary contacts as normally closed contact (EF001377)

1

Number of auxiliary contacts as normally open contact (EF001376)

2

Number of auxiliary contacts as change-over contact (EF003531)

0

Motor drive optional (EF007386)

No

Motor drive integrated (EF006697)

N...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-6-15168/EA/SVB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.