

INDUSTRIAL COMPONENT DATA

T5-7-8349/EA/SVB-SW 094671 Y7-94671 EATON ELECTRIC Industrial Automation Bussines and Industrial Control Dev..

Brand: EATON - MOELLER | Manufacturer Part Number: T5-7-8349/EA/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T5-7-8349/EA/SVB-SW
Catalog number	Y7-94671
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5F3FBA7B54
Generated	2026-08-03

Product Overview

Industrial Automation Bussines and Industrial Control Devices Switching Devices

ON-OFF 13-pole disconnect switch 32 A 90° Flush mount

Main switch according to IEC/EN60947-3, size T5, 690 V/100A, degree of protection Front IP65, lockable in O position with 3 padlocks, design general: insulating material-surface mounting enclosure , flush mounting breaker. High-performance, robust, compact T cam switches are used in industry, the trades , and building services management. A variety of standard switches is available for selection. These are supplemented by special customer-specific switches. Here the possibilities are almost unlimited. Comprehensive accessories complete the switch product range and supplement the usage alternatives. All current paths are equipped with double-break contacts.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

ETIM for 094671 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

No

Version as maintenance-/service switch (EF006986)

No

Version as safety switch (EF006985)

No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current Iu (EF001389)
100 A
Rated permanent current at AC-21, 400 V (EF009165)
100 A
Rated operation power at AC-3, 400 V (EF001364)
30 kW
Rated short-time withstand current Icw (EF007050)
1.7 kA
Rated operation power at AC-23, 400 V (EF007027)
55 kW
Switching power at 400 V (EF009166)
55 kW
Conditioned rated short-circuit current Iq (EF001444)
2 kA
Motor drive optional (EF007386)
No
Motor drive integrated (EF006697)
No
Voltage release optional (EF007491)
No
Device construction (EF008240)
Built-in device fixed built-in technique
Suitable for front mounting 4-hole (EF007247)
No
Suitable for front mounting centre (EF007248)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Colour control element (EF007167)
Black
Type of control element (EF006976)
Door coupling rotary drive
Interlockable (EF006281)
No

Type of electrical connection of main circuit (EF006819)

Screw connection

With pre-assembled cabling (EF016444)

No

Degree of protection (IP), front side (EF003118...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5-7-8349/EA/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.