

## INDUSTRIAL COMPONENT DATA

# P5-XKNB-SW 294130 Y7-294130 EATON ELECTRIC IAB & ICD Switching Devices

Brand: EATON - MOELLER | Manufacturer Part Number: P5-XKNB-SW



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | EATON - MOELLER                  |
| MPN / Reference | P5-XKNB-SW                       |
| Catalog number  | Y7-294130                        |
| Category        | Handle for power circuit breaker |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-ECD1DC0BD5                    |
| Generated       | 2026-08-03                       |

## Product Overview

IAB &amp; ICD Switching Devices

P5-XKNB-SW

Thumb-grip, black, P5

Accessories for main switch/switch-disconnector P5 according to IEC/EN 60947-3, 690 V, degree of protection Front IP65 switch-disconnectors P5 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Disconnectors and Cam Switches

## Additional Product Information

Thumb-grip, black, P5Accessories for main switch/switch-disconnector P5 according to IEC/EN 60947-3, 690 V, degree of protection Front IP65 switch-disconnectors P5 have a very compact and robust design. The manual drive act directly to the connection of the contacts. The contacts are forced open when switching off.Delivery program

BlackDesign verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]0 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-25 °COperating ambient temperature max.+50 °CIEC/EN 61439 design verification10.2 Strength of materials and parts10.2.2 Corrosion resistanceMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosuresMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.2 Verification of

resistance of insulating materials to normal heatMeets the product standard's requirements.10.2 Strength of materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effectsMeets the product standard's requirements.10.2 Strength of materials and parts10.2.4 Resistance to ultra-violet (UV) radiationMeets the product standard's require...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / P5-XKNB-SW with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.