

INDUSTRIAL COMPONENT DATA

T3-5-124/E 004000 Y7-4000 EATON ELECTRIC Multi-speed switches, Contacts: 9, 32 A, One tapped winding, 2 spee..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-124/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-124/E
Catalog number	Y7-4000
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-609E71E59E
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 9, 32 A, One tapped winding, 2 speeds, front plate: 2-0-1, 60 °, maintained, flush mounting, SOND 30

Multi-speed switch 9 poles 32 A 1 threaded winding 2

Eaton Moeller® series T3 Multi-speed switches, T3, 32 A, flush mounting, 5 contact unit(s), Contacts: 9, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 30, Design number 124

Multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 30, Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Multi-speed switch Catalog Number 004000 Model Code T3-5-124/E EAN 4015080040002 Product Length/Depth 125 mm Product Height 54 mm Product Width 61 mm Product Weight 0.292 kg

Certifications CSA Class No.: 3211-05

CSA-C22.2 No. 94

UL File No.: E36332

IEC/EN 60947-3

UL Category Control No.: NLRV

VDE 0660

CSA-C22.2 No. 60947-4-1-14

CE

IEC/EN 60947

CSA File No.: 012528

CSA

IEC/EN 60204

UL 60947-4-1

UL Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 004000 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Dahlander switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

12 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-124/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.