

INDUSTRIAL COMPONENT DATA

Z-SWL230/SS 276306 Y7-276306 EATON ELECTRIC Switch with LED, 230AC/DC, 2N/O, 16A, orange, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SWL230/SS



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SWL230/SS
Catalog number	Y7-276306
Category	Main switch for distribution board
Minimum order	1 Pcs
Document ID	EO-F7D4FE4F48
Generated	2026-08-05

Product Overview

Switch with LED, 230AC/DC, 2N/O, 16A, orange, 1HP

Z-SWL230/SS

Eaton Distribution parts. Switch with LED, 230AC/DC, 2N/O, 16A, orange, 1HP

Switch with LED, function: 2 N/O, rated operational current 16A, rated operating voltage of the switch 250V AC, rated operating voltage of LED 230V AC/DC, color of pushbutton black, color of the LED orange, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 1-10 mm², type conform to IEC/EN 60669, VDE 0632

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 276306 Model Code Z-SWL230/SS EAN 4015082763060 Product Length/Depth 80 mm Product Height 70 mm Product Width 17.5 mm Product Weight 0.065 kg Compliances RoHS conform Product specifications

Fitted with: Signal lamp Equipment heat dissipation, current-dependent 4 W Rated operational voltage (Ue) - max 250 V Voltage rating - min 230 V Width in number of modular spacings 1 Number of poles Two-pole Color calotte Other Switch type Control switch Rated short-time withstand current (Icw) 0.02 kA Lamp socket Other Built-in depth 80 mm Amperage rating 16 A Voltage type AC Lamp type LED Degree of protection IP40 Heat dissipation per pole, current-dependent 2 W Lamp power 2 W Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of

contacts (normally open contacts) 2 Inscription Other Rated operational current for specified heat dissipation (In) 16 A

Rated Switching Capacity 0.016 kA

ETIM for 276306 Modular devices for distribution board/surface mounting (EC001545)

Feature Name

Feature Value

Switching function (EF000189)

Control switch

Number of contacts as normally open contact (EF008256)

2

Number of contacts as normally closed contact (EF008255)

0

Number of contacts as change-over contact (EF008257)

0

Number of poles (EF001391)

2

Rated current (EF000227)

16 A

Rated voltage (EF000228)

250 V

Min. rated voltage (EF005025)

230 V

Rated switching capacity (EF002563)

0.01...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SWL230/SS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.