

INDUSTRIAL COMPONENT DATA

EASY600-POW 262399 EATON ELECTRIC Switched-mode power supply unit, 100-240VAC/24VDC, 4.2A, 1-phase, controll..

Brand: EATON - MOELLER | Manufacturer Part Number: EASY600-POW



Manufacturer	EATON - MOELLER
MPN / Reference	EASY600-POW
Catalog number	262399
Category	PLC system power supply
Minimum order	1 Pcs
Document ID	EO-502AF41416
Generated	2026-08-06

Product Overview

Switched-mode power supply unit, 100-240VAC/24VDC, 4.2A, 1-phase, controlled

Switching power supply; 100-240 V AC/24 V DC; 4.2A; Single phase

The primary cycled and controlled switched-mode power supply units supply a safe low voltage (SELV according to EN 60 950) with radio interference level B according to EN 55 011 and EN 55 022. They have been tested for use in industrial as well as public networks. Overload safety and permanent short-circuit strength ensure for a high safety of the devices. Rated input voltage at 50/60 Hz: 100-240VAC, rated output voltage: 24VDC with a residual ripple of $\pm 3\%$ rated output current: 4.2A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > EASY programmable relays and MFD displays

Additional Product Information

Switched-mode power supply unit, 100-240VAC/24VDC, 4.2A, 1-phase, controlledThe primary cycled and controlled switched-mode power supply units supply a safe low voltage (SELV according to EN 60 950) with radio interference level B according to EN 55 011 and EN 55 022. They have been tested for use in industrial as well as public networks. Overload safety and permanent short-circuit strength ensure for a high safety of the devices. Rated input voltage at 50/60 Hz: 100-240VAC, rated output voltage: 24VDC with a residual ripple of $\pm 3\%$ rated output current: 4.2A

Delivery program

Product rangeControl relay easyRelay

Multi-function-display MFD-TitanProduct rangeSwitched-mode power supply units easyPOWDescriptionprimary chopper

controlledPhasesSingle-phaseInput voltage range85 - 264 V ACNominal input voltage100 - 240 V ACRated output voltage24 V DC ($\pm 3\%$)Rated output current4.2 AFor use witheasy500

easy700

easy800

MFD-CP8

EC4P

ES4PTechnical data

GeneralStandardsEN 55011, EN 55022, IEC/EN 61000-4, IEC 60068-2-6, IEC 60068-2-27Dimensions (W x H x D)107.5 (6 PE) x 90 x 58 mmWeight0.3 kgMountingTop-hat rail IEC/EN 60715, 35 mm or screw fixing using fixing brackets ZB4-101-GF1 (accessories)Terminal capacitiesSolid0.2/4 (AWG 22 - 12) mm²Flexible with ferrule0.2/2.5 (AWG 22 - 12) mm²Standard screwdriver0.8 x 3.5 mmMax. tightening torque0.6 NmClimatic environmental conditionsOperating ambient temperature-25 to 55, cold as per IEC 60068-2-1, heat as per IEC 60068-2-2 °CCondensationTake appro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EASY600-POW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.