


INDUSTRIAL COMPONENT DATA

T0-1-15482/XZ 009318 Y7-9318 EATON ELECTRIC ON-OFF switches, Contacts: 2, 20 A, 90 °, rear mounting, Basic s..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-15482/XZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-15482/XZ
Catalog number	Y7-9318
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-D5A46F8D8C
Generated	2026-08-04

Product Overview

ON-OFF switches, Contacts: 2, 20 A, 90 °, rear mounting, Basic switch

Disconnect switch ON-OFF; 2-pole; 20 A; 90 °; Mounting bottom panel; Switch replacement part for case

ON-OFF switches, T0, 20 A, rear mounting, Basic switch, 1 contact unit(s), Contacts: 2, 90 °, design no. 15482

On-Off switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 2, Design: rear mounting, Basic switch, Switching angle: 90 °, 1 contact unit(s), Rated uninterrupted current: I_u= 20 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

ON-OFF switches, T0, 20 A, rear mounting, Basic switch, 1 contact unit(s), Contacts: 2, 90 °, design no. 15482 On-Off switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 2, Design: rear mounting, Basic switch, Switching angle: 90 °, 1 contact unit(s), Rated uninterrupted current: I_u= 20 A Delivery program

Product range Control switches Part group reference T0 Basic function ON-OFF switches Contacts 2 Design rear mounting Basic switch Contact sequence Switching angle 90 ° Design number 15482 Front plate no. Motor rating AC-23A, 50 - 60 Hz [P] 400 V [P] 5.5 kW Rated uninterrupted current [I_u] 20 A Note on rated uninterrupted current I_u Rated uninterrupted current I_u is specified for max. cross-section. Number of contact units 1 contact unit(s) Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3 Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Ambient temperature Open-25 - +50 °C Ambient temperature Enclosed-25 - +40 °C
Overvoltage category/pollution degree III/3 Rated impulse withstand voltage [Uimp] 6000 V AC Mechanical shock resistance 15 g Mounting position As required Contacts Electrical characteristics Rated operational voltage [Ue] 690 V AC
Electrical characteristics Rated uninterrupted current [Iu] 20 A Electrical characteristics Note on rated uninterrupted current
!u Rated uninterrupted curre...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-15482/XZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.