

INDUSTRIAL COMPONENT DATA

T0-2-1/ST/SVB-SW 201713 EATON ELECTRIC Main switch, +steel enclosure, 3p, Ie 12A, handle black, 0-1, 90°

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-1/ST/SVB-SW



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-1/ST/SVB-SW
Catalog number	201713
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-F9D204E5BA
Generated	2026-08-06

Product Overview

Main switch, +steel enclosure, 3p, Ie=12A, handle black, 0-1, 90°

General switch; 3-pole; 20 A; 90 °; Mounting stainless steel box; Lever Black; Lockable in the 0 position (OFF)

Main switch according to IEC/EN60947-3, size T0 in steel sheet enclosure, 690 V/20A, degree of protection Front IP55, with black rotary handle and black locking collar, lockable in 0 position with 3 padlocks, design general: insulating material-surface mounting enclosure , flush mounting, center mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork , and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities. All contacts are equipped with double interrupting contacts.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Main switch, +steel enclosure, 3p, Ie=12A, handle black, 0-1, 90°Main switch according to IEC/EN60947-3, size T0 in steel sheet enclosure, 690 V/20A, degree of protection Front IP55, with black rotary handle and black locking collar, lockable in 0 position with 3 padlocks, design general: insulating material-surface mounting enclosure , flush mounting, centre mounting, rear mounting IVS service distribution board mounting. The capable, robust, compact T cam switches are used in industry, handwork, and building services management. A variety of standard circuits are available for selection. Special customer-specific circuits are implemented as supplements. The possibilities are almost unlimited here. Comprehensive accessories complete the switch range and supplement application possibilities. All contacts are equipped with double

interrupting contacts.Delivery program

Product rangeMain switch

maintenance switch

Repair switchPart group referenceT0Stop FunctionSTOP functionWith black rotary handle and locking ringNumber of

poles3 poleLocking facilityLockable in the 0 (Off) positionDegree of ProtectionIP65Designsurface mountingContact

sequenceDesign number1FunctionMotor rating AC-23A, 50 - 60 Hz [P]400 V [P]5.5 kWRated uninterrupted current [Iu]20

ANote on rated uninterrupted current !uRated uninterrupted current Iuis specified for max. cross-section.Number of contact

units2 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector ac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-1/ST/SVB-SW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.