

INDUSTRIAL COMPONENT DATA

T0-3-15064/Z 012871 Y7-12871 EATON ELECTRIC

Spring-return switch, Contacts: 6, 20 A, front plate: 0-1 Spri..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-15064/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-15064/Z
Catalog number	Y7-12871
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-AB093AACD2
Generated	2026-08-02

Product Overview

Spring-return switch, Contacts: 6, 20 A, front plate: 0-1

Spring-return switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: momentary, With 0 (Off) position, with spring-return from both directions, 3 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 0-1

Switch with return; 6-pole; 20a; rating Plate: 0-1

Eaton Moeller® series T0 Spring-return switch, T0, 20 A, rear mounting, 3 contact unit(s), Contacts: 6, 45 °, momentary, With 0 (Off) position, with spring-return from both directions, 0-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Spring-return switch Catalog Number 012871 Model Code T0-3-15064/Z EAN 4015080128717 Product Length/Depth 137 mm Product Height 48 mm Product Width 48 mm Product Weight 0.163 kg
Certifications IEC/EN 60947-3
IEC/EN 60947

IEC/EN 60204

CSA File No.: 012528

UL File No.: E36332

UL Category Control No.: NLRV

CE

UL

VDE 0660

CSA-C22.2 No. 94

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-05

CSA Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 012871 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

On/Off switch

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-15064/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.